

S 型中开式单级双吸离心泵性能参数

型号	流量	扬程	转速	功率 (kw)		效率	汽蚀余量
	(m ³ /h)	(m)	(r/min)	轴功率	电机功率	(%)	(m)
100S90	80	90	2950	30.1	37	65	2.5
100S90A	72	75	2950	23	30	64	2.5
150S100	160	100	2950	59.8	75	73	3.5
150S78	160	78	2950	45	55	75.5	3.7
150S78A	144	62	2950	33.4	45	72.6	3.7
150S50	160	50	2950	27.3	37	80.4	3.9
150S50A	144	40	2950	20.0	30	75.5	3.9
150S50B	133	36	2950	18.0	22	72.5	3.9
200S95	280	95	2950	91.4	132	79.2	5.3
200S95A	270	85	2950	83.3	110	75	5.3
200S95B	260	75	2950	73.8	90	72	5.3
200S63	280	63	2950	58.3	75	82.7	5.8
200S63A	270	46	2950	45.1	55	75	5.8
200S42	280	42	2950	38.1	45	84.2	6
200S42A	270	36	2950	33.1	37	80	6
250S65	485	65	1450	109.2	132	78.6	3.1
250S65A	420	48	1450	88.5	90	77.7	3.1
250S39	485	39	1450	61.5	75	83.6	3.2
250S39A	468	30	1450	48.4	55	79	3.2
250S24	485	24	1450	36.9	45	85.8	3.5
250S24A	414	20	1450	27.2	37	83.3	3.5
250S14	485	14	1450	21.5	30	85.8	3.8
250S14A	432	11	1450	15.2	18.5	82.7	3.8
300S90	790	90	1450	243	320	79.6	4.2
300S90A	756	78	1450	216.4	280	74.2	4.2
300S90B	720	67	1450	180	220	73	4.2
300S58	790	58	1450	147.9	200	84.2	4.4
300S58A	720	49	1450	118.0	160	82.5	4.4
300S58B	684	43	1450	100	132	80	4.4
300S32	790	32	1450	79	90	86.8	4.6
300S32A	720	26	1450	60.7	75	84	4.6
300S19	790	19	1450	47.1	55	86.8	5.2
300S19A	720	16	1450	39.2	45	80	5.2
300S12	790	12	1450	30.4	37	84.8	5.5
300S12A	684	10	1450	23.9	30	78.4	5.5

350S125	1260	125	1450	533	680	80.5	5.4
350S125A	1181	112	1450	461	570	78.2	5.4
350S125B	1098	96	1450	373	500	77	5.4
350S75	1260	75	1450	303	360	85.2	5.8
350S75A	1170	65	1450	244.4	280	84.2	5.8
350S75B	1080	55	1450	196.3	220	82.4	5.8
350S44	1260	44	1450	172.5	220	87.5	6.3
350S44A	1116	36	1450	129.5	160	84.5	6.3
350S26	1260	26	1450	102	132	87.5	6.7
350S26A	1116	21	1450	76.9	90	83.4	6.7
350S16	1260	16	1450	64.4	75	85.4	7.1
350S16A	1044	13	1450	47	55	78.3	7.1
400S90	1620	90	1450	473	560	84	6.2
400S90A	1460	73	1450	345	450	84	6.2
400S90B	1300	58	1450	245	315	84	6.2
400S40	1080	40	970	140	185	85	5.1
400S40A	1007	33	970	107	160	84.5	5.1
400S40B	870	26	970	73.3	110	84	5.1
500S98	2020	98	970	678.1	800	79.5	4.1
500S98A	1872	83	970	539	630	78.5	4.1
500S98B	1746	74	970	450.1	560	78.7	4.1
500S59	2020	59	970	388.2	450	83.6	4.5
500S59A	1872	49	970	332.32	400	75.6	4.5
500S59B	1746	40	970	255.8	315	74	4.5
500S35	2020	35	970	218.2	280	83.6	4.8
500S35A	1746	27	970	150.6	220	75.6	4.8
500S22	2020	22	970	143.6	185	74	5.2
500S22A	1746	17	970	100.6	132	88.2	5.2
500S13	2020	13	970	85.7	110	85.2	5.7
600S22	3170	22	970	215.8	250	84.2	7
600S22A	2860	18	970	161.1	185	80.3	7
600S32	3170	32	970	310.4	355	83.4	7
600S32A	2850	26	970	229	280	88	7
600S47	3170	47	970	456	560	87	6.5
600S47A	2920	40	970	361	450	89	6.5
600S75	3170	75	970	736	900	88	6
600S75A	2920	65	970	600.2	710	89	6
600S75B	3170	55	970	477.5	560	88	6

600S100	2950	100	970	1015.6	1250	87	6
600S100A	2710	90	970	875.4	1120	85	6
600S100B	3170	80	970	751.9	900	85	6
800S22	3000	22	730	370.2	450	84	7
800S22	2830	14	585	190.6	250	82	5
800S22A	5500	17	730	254.1	315	89	7
800S22A	4400	11	585	133.3	185	88	5
800S32	4830	32	730	538.5	630	87	74.5
800S32	3870	20	585	272.3	315	89	7
800S32A	5500	26	730	389	450	88	4.5
800S32A	3960	17	585	210.7	250	88	6.5
800S47	5500	47	730	782.2	1000	87	4.2
800S47	4400	30	585	403.9	450	90	6.5
800S47A	5070	40	730	621	710	89	4.2
800S47A	4060	25	585	314.1	355	89	6
800S76	5500	76	730	1293.6	1600	88	4.2
800S76	4400	49	585	674.9	800	88	6
800S76A	5080	65	730	1034	1250	87	6
800S76A	4070	42	585	541	630	86	4.2
800S76B	4680	55	730	824.7	1000	85	6
800S76B	3750	35	585	425.5	500	84	4