

MP 型塑料磁力驱动循环泵性能参数表

型号	普通型 软管接口		螺纹接口		最大 流量 (L/min)	最高 扬程 (m)	标准输出		介质 密度 (g/cm ³)	电机 功率 (W)	转速 (r/min)	电压 (V)
	进口 (mm)	出口 (mm)	进出口 (inch)	活管 (mm)			流量 (L/min)	扬程 (m)				
MP-6R	14	14	-	-	8	1	2.8	0.8	<1.2	3	2900	220
MP-6RZ	14	14	-	-	5.5	2.1	3.2	0.8	<1.1	3	2900	220
MP-10R	14	14	-	-	11	1.5	5	1	<1.1	6	2900	220
MP-15R	16	16	-	-	16	2.7	8	1.5	<1.3	10	2900	220
MP-15RM	-	-	3/4	13	16	2.4	8	1.5	<1.3	10	2900	220
MP-20R	18	18	-	-	27	3.1	17	2	<1.2	20	2900	220
MP-20RM	-	-	3/4	16	27	3.1	17	2	<1.2	20	2900	220
MP-20RX	26	26	-	-	46	1.8	30	1	<1.3	20	2900	220
MP-20RZ	18	18	-	-	10	4.6	7	4	<1.1	20	2900	220
MP-30R	20	20	-	-	33	3.8	16	2.5	<1.3	45	2900	220
MP-30RM	-	-	3/4	16	33	3.8	16	2.5	<1.3	45	2900	220
MP-30RX	26	26	-	-	62	2.9	32	2	<1.1	45	2900	220
MP-30RZ	18	18	-	-	15	8	10	6	<1.1	45	2900	220
MP-30RZM	-	-	3/4	13	15	8	10	6	<1.1	45	2900	220
MP-40R	20	20	-	-	45	4.6	22	4	<1.1	65	2900	220
MP-40RM	-	-	3/4	16	46	4.6	22	4	<1.1	65	2900	220
MP-40RX	26	26	-	-	75	3.3	47	2	<1.1	65	2900	220
MP-55R	26	26	-	-	60	5.6	30	4	<1.2	90	2900	220/380
MP-55RM	-	-	1	20	60	5.6	30	4	<1.2	90	2900	220/380
MP-55RZ	26	26	-	-	25	10	15	8	<1.1	90	2900	220/380
MP-70R	26	26	-	-	86	6.7	50	4	<1.1	150/18	2900	220/380

										0		
MP-70RM	-	-	1	20	86	6.7	50	4	<1.1	150/180	2900	220/380
MP-100R	26	26	-	-	120	8.6	60	7	<1.3	250/265	2900	220/380
MP-100RM	-	-	1	20	120	8.6	60	7	<1.3	250/265	2900	220/380
MP100RX	-	-	1	32	170	9	100	5	<1.3	250	2900	220/380
MP-120R	-	-	1	36	220	10.5	140	6	<1.3	370	2900	220/380
MP-400	-	-	1	36	220	12.5	150	8	<1.3	370	2900	220/380
MP-401	-	-	1	36	260	18	120	12	<1.3	750	2900	380
MP-422	-	-	2	40	320	21	160	18	<1.3	1500	2900	380
MP-423	-	-	2	40	380	22	230	18	<1.3	2200	2900	380
MP-424	-	-	2	40	410	35.5	208	32	<1.3	3000	2900	380