

ZJ 型纸浆泵性能参数表

流量列：括号外数字表示额定点，括号内数字表示使用范围；扬程列同类。

型号	流量	扬程	转速	效率	汽蚀 余量	电机功率		泵口径	
	(m <sup>3</sup> /h)					(m)	(r/min)	(%)	(m)
65ZJ25-12	25(15-40)	12(9-14)	1450	55	3.4	2.2	3	80	65
65ZJ25-18	25(15-40)	18(15-21)	1450	53	3.4	4	5.5	80	65
65ZJ25-27	25(15-40)	27(24-30)	1450	51	3.4	5.5	7.5	80	65
65ZJ25-45	25(15-40)	45(40-49)	1450	49	3.4	11	15	80	65
80ZJ40-12	40(25-60)	12(9-14)	1450	64	3.7	3	4	100	80
80ZJ40-18	40(25-60)	18(15-21)	1450	61	3.7	5.5	7.5	100	80
80ZJ40-27	40(25-60)	27(24-30)	1450	59	3.7	7.5	11	100	80
80ZJ40-45	40(25-60)	45(40-49)	1450	56	3.7	15	18.5	100	80
100ZJ70-12	70(40-110)	12(9-15)	1450	71	4.0	5.5	7.5	150	100
100ZJ70-18	70(40-110)	18(15-22)	1450	67	4.0	7.5	11	150	100
100ZJ70-27	70(40-110)	27(24-31)	1450	65	4.0	11	15	150	100
100ZJ70-45	70(40-110)	45(40-50)	1450	62	4.0	22	30	150	100
150ZJ120-12	120(70-180)	12(10-15)	1450	70	4.5	7.5	11	200	150
150ZJ120-18	120(70-180)	18(15-23)	1450	67	4.5	15	18.5	200	150
150ZJ120-27	120(70-180)	27(24-31)	1450	65	4.5	18.5	30	200	150
150ZJ120-45	120(70-180)	45(40-50)	1450	60	4.5	37	45	200	150
150ZJ210-12	210(125-315)	12(10-15)	1450	74	5.0	15	18.5	200	150
150ZJ210-18	210(125-315)	18(15-23)	1450	73	5.0	22	30	200	150
150ZJ210-27	210(125-315)	27(24-31)	1450	71	5.0	30	45	200	150
150ZJ210-45	210(125-315)	45(40-50)	1450	67	5.0	55	75	200	150
200ZJ370-12	370(200-540)	12(10-15)	1450	74	5.6	22	30	250	200
200ZJ370-18	370(200-540)	18(15-23)	1450	74	5.6	37	45	250	200
200ZJ370-27	370(200-540)	27(24-31)	1450	73	5.6	55	75	250	200
200ZJ370-45	370(200-540)	45(40-50)	1450	71	5.6	90	132	250	200
200ZJ500-12	500(300-800)	12(9-15)	1450	75	6.4	30	37	250	200
200ZJ500-18	500(300-800)	18(15-23)	1450	76	6.4	45	55	250	200
200ZJ500-27	500(300-800)	27(23-31)	1450	75	6.4	75	90	250	200
200ZJ500-45	500(300-800)	45(40-51)	1450	73	6.4	132	160	250	200
300ZJ1000-27	1000(800-1200)	27(24-31)	1450	74	7.2	132	160	350	300